

Deck-Drive™ DWP WOOD SS Screw



The DWP softwood-to-softwood screw is a powerful fastening solution for decking and general exterior applications where extra corrosion protection is required. With its specially designed sharp-point tip and unique box-thread design the DWP is suited to a majority of softwood timber used for decking.

Features

- Box thread design with raised-ridge technology greatly reduces driving torque, which allows you to drive more screws on a single battery charge
- 305 Stainless Steel where extra corrosion protection is required, ideal for outdoor exposure and wet service environments
- Specially-designed sharp point penetrates softwood timber products with ease
- 6-lobe drive helps prevent driver-bit cam-out, resulting in easier driving and longer bit life

Application

- Decking
- Maximum recommended board thickness:
50 mm screw — 20 mm; 65 mm screw — 25 mm

Finish

- **305 Stainless Steel**




T-25, 6-lobe drive reduces cam-out, making driving easier



Box thread greatly reduces driving torque



Sharp point easily penetrates softwood timber decking



Scan this QR code to watch video of Deck-Drive™ DWP Wood Screw.
<https://youtu.be/EBtsqyp3JDY>

10 Gauge Softwood-to-Softwood

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit
S10200WPR250	4.9mm	50mm	Box Thread	Sharp Point	250	6-lobe T-25	BIT25T-2-RC3
S10200WPR1100 *					1100		
S10250WPR250		65mm			250		
S10250WPR1100 *					1100		

*Only available in New Zealand.
Predrilling and countersinking may be required.