

Deck-Drive™ DHW HARDWOOD-TO-SOFTWOOD Screw



The DHW is a premium decking fastener designed for no predrilling in hardwood decking applications. The winged design and hardwood drill point virtually eliminates splitting of timber without predrilling in the hardest timber applications.

Features

- Compact head for countersunk finish and discreet appearance
- Designed to penetrate the hardest timber without predrilling
- Wings on the shaft counter-bore hard timber to allow the head to countersink for clean look
- Available in Class 3 Galvanised or for additional corrosion protection 305 Stainless Steel

Application

- Hardwood decking and exterior hardwood-to-softwood
- Maximum recommended board thickness 20 mm

Finish

- Class 3 Galvanised (DHWG60R250)
- **305 Stainless Steel** (SSDHW60R250, SSDHW60R1100)



This screw is also available collated for the Quik Drive® system. See page 189 for details.



Compact head countersinks easily.



Winged design easily bores out hardwood to allow head to countersink perfectly.



Hardwood drill point requires no predrilling.

PLEASE NOTE: Refer to pages 19–26 for use of galvanised decking fasteners.

10 Gauge Hardwood-to-Softwood

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit
DHWG60R250	4.9mm	60mm	Coarse Threads	Hardwood Drill Point	250	#2 Undersize Square Drive	BIT2SU-2-RC3
SSDHW60R250						#2 Square Drive	BIT2S-2-RC3
SSDHW60R1100 *					1100		

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.

*Only available in New Zealand.