

## Deck-Drive™ DHSD HARDWOOD-TO-HARDWOOD Screw



The DHSD Hardwood-to-Hardwood screw is ideal for hardwood decking applications and is specifically designed to penetrate the hardest timber with ease. The unique drill point virtually eliminates splitting all without the need of predrilling. The raised compact head delivers a professional finish for a decorative style deck.

### Features

- Raised countersinking head
- Unique ribbed shank provides greater strength and holding power
- Design virtually eliminates splitting of hardwood decking
- No predrilling required in hardwood joists

### Application


- Hardwood to hardwood decking applications
- Maximum recommended board thickness:  
50 mm screw — 20 mm; 60 mm screw — 25 mm

### Finish

- 305 Stainless Steel



*This screw is also available collated for the Quik Drive® system. See page 190 for details.*



**Raised compact head** for a decorative finish



**Ribbed shank** provides greater holding power



**Hardwood drill point** virtually eliminates splitting and the need for predrilling

## 10 Gauge Hardwood-to-Hardwood

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit
SSDHSD50R250	4.9mm	50mm	Coarse Threads	Hardwood Drill Point	250	#2 Square Drive	BIT2S-2-RC3
SSDHSD50R1100 *					1100		
SSDHSD60R250		60mm			250		
SSDHSD60R1100 *					1100		

\*Only available in New Zealand.