

Deck-Drive™ DCSD COMPOSITE-TO-STEEL Screw



The DCSD Composite-to-steel screw is designed to easily drive through composite decking into 0.8–2.4 mm steel. The special cap head provides a clean, less noticeable installation and is available in 4 colours to suit composite timber.

Features

- Drives easily through 0.8–2.4 mm steel without predrilling
- Compact head provides a clean, finished deck surface with no mushrooming
- Available in 4 colours

Application

- Composite-to-steel decking
- Recommended steel thickness 0.8–2.4 mm
- Maximum recommended board thickness 25 mm

Finish

- Quik Guard® coating

Corrosion Resistance Level
MEDIUM

This screw is also available collated for the Quik Drive® system. See page 193 for details.



Cap head for a cleaner less noticeable fixing



Inverted upper threads clear excess material to ensure the screw is seated properly and consistently



Drill flute ejects composite material for easier installation

10 Gauge Composite-to-Steel Screw

Bit(s) included with every box of screws

Model No.	Colour	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit
DCSD238BRR250	Brown	4.9mm	60mm	16 TPI	#2 Drill point	250	#2 Undersize Square Drive	BIT2SU-2-RC3
DCSD238GRR250	Grey							
DCSD238RDR250	Red							
DCSD238TNR250	Tan							

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.