



Deck-Drive™ DHW HARDWOOD-TO-SOFTWOOD Screw



The DHW is a premium decking fastener designed for no predrilling in hardwood decking applications. The winged design and hardwood drill point virtually eliminates splitting of timber without predrilling in the hardest timber applications.

Features


- Compact head for countersunk finish and discreet appearance
- Designed to penetrate the hardest timber without predrilling
- Wings on the shaft counter-bore hard timber to allow the head to countersink for clean look
- Available in Class 3 Galvanised or for additional corrosion protection 305 Stainless Steel

Application

- Hardwood decking and exterior hardwood-to-softwood joist
- Maximum recommended board thickness 20 mm

Finish

- Class 3 Galvanised (DHW60SA)
- **305 Stainless Steel** (SSDHW60SA)



This screw is also available loose for hand-drive installation. See page 146 for details.



Compact head countersinks easily.



Winged design easily bores out hardwood to allow head to countersink perfectly.



Hardwood drill point requires no predrilling.

PLEASE NOTE: Refer to pages 19–26 for use of galvanised decking fasteners.

10 Gauge Hardwood-to-Softwood Screw

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit	PRO 200	PRO 250	PRO 300
DHWG60SA	4.9mm	60mm	Coarse Threads	Hardwood Drill Point	1,000	#2 Undersize Square Drive	BIT2SU-RC10	—	✓	✓
SSDHW60SA						#2 Square Drive	BIT2S-RC10	—	✓	✓

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.