

PRO250G2B25KA

QUIK DRIVE® Auto-Feed System For Flooring, Decking and Wall Plates



The Simpson Strong-Tie® Quik Drive® PRO250G2 auto-feed screw driving system ideal, but not limited to subfloor and decking applications, due to the holding power of screws that reduce gaps that cause floor squeaks, also screws prevent fastener heads from popping up above the boards.

Features:

- Expanded depth settings for high-density flooring materials
- Reversible and replaceable non-skid teeth
- Uniform toenailing and countersink on slick surfaces
- Rigid strip collation prevents jamming
- Drive 8–10g (4.2–4.9mm) and 40–65mm length screws

Applications:

- Timber-to-Timber or Timber-to-Steel
- Subflooring-to-Timber or Subflooring-to-Steel
- Fibre Cement-to-Timber or Fibre Cement-to-Steel
- Decks and docks

System Includes:

- QDPRO250G2 auto-feed attachment
- Extension pole QDEXTG2 (515mm)
- Bosch® GSR 6-25 TE Professional 701 W, No load speed of 0–2500 rpm, Rated Torque 2, 3 Nm, BOA1G2 adaptor fitted
- Quiver for keeping screws at your fingertips
- Protective tool case
- Spare PMANDREL75



Quik Drive® auto feed screw-driving systems by Simpson Strong-Tie create a wide range of sales opportunities for dealers. With a broad assortment of professional-grade attachments and quick-loading fastener strips for many applications, Quik Drive tools help ensure steady, repeat sales. And with a lifetime warranty and the strength of the Simpson Strong-Tie® distribution network behind it, Quik Drive systems provide reliable delivery to keep your inventory at optimal levels. See www.strongtie.com.au/info and the *Fastening Systems* catalog for coating and corrosion information.

Subfloor, Wall Plate and Deck Screws available for the PRO250G2B25KA



WSNTL Series – Wood Screws

Twin thread, sharp point, countersink nibs, yellow zinc coating, #3 square drive


WSNTLA134SA: 4.5 x 45mm

WSNTLA2SA10: 4.9 x 50mm (complies with AS1860)

WSNTLG2S: 4.5 x 50mm (Class 3 mechanically galvanized coating – complies with AS 3566)

WSNTL212SA: 4.5 x 65mm

- Drive up to 40% faster than single thread screws
- Ideal for high density particle board flooring and sheathing



PPSD11516SA – Plywood-to-Steel Screw

Fine thread, #2 drill point, flat head, yellow zinc coating, #3 square drive

PPSD11516SA: 4.2 x 50mm

- Engineered for steel framing up to 2.4mm – prevents floor material (*up to 19mm*) from “riding up” threads



CBSDG Series – Winged Self-Drilling Screws

Fine thread, #2 drill point with wings, Class 3 mechanically galvanized coating – complies with AS 3566, #2 square drive, 30 screws per strip

CBSDG158SA: 4.2 x 42mm

CBSDGL158SA: 4.9 x 42mm

CBSDGL214SA: 4.9 x 55mm

- Engineered to fasten cement board and particle board to steel framing (1.5 – 3mm thick)




DTHG Series – Trim Head Deck Screws

Coarse thread, type 17 point, countersink nibs, Class 3 mechanically galvanized coating – complies with AS 3566, #2 square drive

DTHG2SA: 4.2 x 50mm

DTHG212SA: 4.2 x 65mm

- Type 17 point for easy, straight drive
- Trim head for neat appearance
- Ideal for softwood decking




WSCBGA158SA Screw

Type 17 sharp point, cement board to timber, countersink nibs, Class 3 mechanically galvanized coating – complies with AS 3566, #2 square drive

WSCBG158SA: 4.5 x 42mm

- Type 17 point for easy, straight drive
- Nibs for countersink in tough materials



SSWSC2BSA10 Screw

Coarse thread, type 17 point, 305 stainless steel, #3 square drive

SSWSC2BSA10: 4.9 x 50mm

- High corrosion resistance
- Type 17 notched point for easier driving

Note: Stainless-steel screws may require pre-drilling in certain high-density materials.



SSDTH Series – Stainless Steel Screws

Box thread, 305 stainless steel, #2 square drive

SSDTH2SA (Trim Head): 4.3 x 50mm

SSDTH212SA (Trim Head): 4.3 x 65mm

- High corrosion resistance
- Ideal for softwood decking


Note: Stainless-steel screws may require pre-drilling in certain high-density materials.



DCL Series – Composi-lok™ Screws for Composite Decking

Cap head, sharp point, Quik Guard® coating, #2 undersized square drive

- “Wings” on the shaft pre-drill the composite decking boards, creating a channel for excess material and preventing the screw from “spinning out”
- Cap head prevents any mushrooming material for a clean-looking installation
- Available in gray, tan, red and brown to match composite deck boards, or in type 305 stainless steel for premium corrosion resistance



DHPD Series – Hardwood Deck Screw

Compact head, type 305 stainless steel or Class 3 mechanically galvanized coating – complies with AS 3566, paddle-style drill point, #2 square drive

DHPD212SA: 4.9 x 65mm

SSDHPD212SA: 4.9 x 65mm

- Reinforced wings for countersinking

(See www.strongtie.com.au/info and the *Quik Drive® Auto-Feed Screw Driving Systems* catalog for coating and corrosion information.)



New Nose Clip for Decking Applications

Achieve perfectly spaced deck boards and screws without measuring or guessing. The Simpson Strong-Tie® Quik Drive® PDECKNC-RC decking nose clip fits onto the end of all PRO250G2 auto-feed screw driving attachments and acts as a guide to ensure proper placement of screws when attaching deck boards to joists. The nose clip kit contains a guide for either a 3mm or a 5mm gap between decking boards. The prongs on the nose clip guide the tool into the correct position, ensuring screws are installed in a straight line every time. Refer to www.strongtie.com.au for more information on the PDECKNC-RC decking nose clip.

Simpson Strong-Tie® Australia Pty. Limited

Unit 1/16 Kenoma Place
Arndell Park, NSW 2148
Tel: +61 2 98317700
ABN No.: 59 088883863
Fax: +61 298312726
www.strongtie.com.au

New Zealand branch
28 Arrenway Drive
Albany, Auckland 0632
Tel: 09 4774440
Fax: 09 4759724
www.strongtie.co.nz