

# ETR Crack Injection Paste-Over Adhesive

## SAFETY DATA SHEET

### 1. Identification

#### Product Identification

Product Identifier:	ETR
Recommended Use:	Epoxy Paste-Over Material for Crack Repair
Use Restrictions:	None Known.
UN Number:	2735
Proper Shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (Diethylenetriamine), 8, III
DG Class:	8
Packing Group:	III
Hazchem Code:	2X

#### Company Identification

<b>Company:</b> Simpson Strong-Tie Australia Pty Limited	<b>Company:</b> Simpson Strong-Tie New Zealand
<b>Address:</b> Unit 1/16 Kenoma Place Arndell Park, NSW 2148 Australia	<b>Address:</b> 28 Arrenway Drive Albany, Auckland 0632 New Zealand
<b>Phone:</b> +612 9831 7700	<b>Phone:</b> +64 9 477 4440
<b>Website:</b> www.strongtie.com.au	<b>Website:</b> www.strongtie.co.nz
<b>Emergency:</b> 13 11 26	<b>Emergency:</b> 0800 POISON (0800 764 766)

### 2. Hazard Identification

#### General Information

ETR is a two part system. The two parts of this product have been assessed according to GHS and are classified below. The final hardened material is considered nonhazardous. Some hazards apply upon grinding or cutting through hardened product.

#### Part A (white side) GHS Classification

##### Classification

Physical Hazards:	Not Classified.	
Health Hazards	Skin Corrosion/Irritation	Category 2
	Serious Eye Damage/Irritation	Category 2A
	Sensitization, Skin	Category 1
	Germ Cell Mutagenicity	Category 2
	STOT, Single Exposure	Category 2 (narcotic effects)
Environmental Hazards:	Acute Aquatic Environmental Hazard	Category 2
	Chronic Aquatic Environmental Hazard	Category 2

##### Label Elements



Health Hazard



Exclamation Mark



Environment

##### Signal Word:

**WARNING!**

##### Hazard Statements:

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

##### Precautionary Statements:

###### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid release to the environment.

###### Response:

If exposed or concerned: Call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before re-use. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

# ETR Crack Injection Paste-Over Adhesive

## SAFETY DATA SHEET

**Storage:**  
**Disposal:**

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
Collect Spillage.  
Store locked up. Store in a well-ventilated place. Store between 45-90°F (7-32°C).  
Dispose of contents/container in accordance with local/regional/national/international regulations.

### Part B (black side) GHS Classification

#### Classification

<b>Physical Hazards:</b>	Flammable Liquid	Category 4
<b>Health Hazards:</b>	Skin Corrosion/Irritation	Category 1C
	Serious Eye Damage/Irritation	Category 1
	Sensitization, Skin	Category 1
	STOT, Single Exposure	Category 2 (narcotic effects)
<b>Environmental Hazards:</b>	Not Classified.	

#### Label Elements



Corrosion



Exclamation Mark

**Signal Word:**  
**Hazard Statements:**

**DANGER!**  
Combustible liquid. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause drowsiness or dizziness.

**Precautionary Statements:**  
**Prevention:**

Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid breathing dust/fume/ gas/mist/vapors/spray.

**Response:**

If swallowed: Rinse mouth. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before re-use.

**Storage:**  
**Disposal:**

Store locked up. Store in a well-ventilated place. Store between 45-90°F (7-32°C).  
Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured components of ETR. Upon combination with the components of ETR form an innocuous solid which does not present any immediate hazards. Upon grinding or cutting the cured product, the following hazards may apply.



**Health Hazards:**  
**Hazard Statements:**  
**Precautionary Statements:**

Carcinogenicity  
Suspected of causing cancer.  
Do not breathe dust.

Category 2

### 3. Composition Information

#### General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

# ETR Crack Injection Paste-Over Adhesive

## SAFETY DATA SHEET

### Part A (white side)

Chemical Name	CAS Number	Weight %
Bisphenol A/Epichlorohydrin	25068-38-6	40-60
Wollastonite	13983-17-0	20-30
Limestone	1317-65-3	10-20
o-Cresyl Glycidyl Ether	2210-79-9	1-10
Titanium Dioxide	13463-67-7	1-5

### Part B (black side)

Chemical Name	CAS Number	Weight %
Wollastonite	13983-17-0	35-50
Polymercaptan	N/A	15-30
Diethylenetriamine	111-40-0	1-10
Limestone	1317-65-3	1-10
Terpene Hydrocarbon	8002-09-3	1-10

## 4. First-Aid Measures

### General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. You should call the Poisons Information Center if you feel you may have been harmed, burned, or irritated by this product. The number is 13 11 26 (24hr). Ready access to running water and accessible eyewash is required. Wash contaminated clothing before reuse.

### Routes of Exposure

- Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician.**
- Skin Contact:** Remove contaminated clothing and product, immediately wash affected area with soap and water. If skin irritation persists **consult a physician.**
- Ingestion:** Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. **Consult a physician.**
- Inhalation:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

### Most Important Symptoms

Symptoms include itching, burning, redness and tearing. Sensitization. Rash. Drowsiness and dizziness. Headaches, nausea and vomiting. Corrosive effects. Permanent eye damage including blindness could result.

## 5. Fire-Fighting Measures

- Suitable Extinguishing Media:** Extinguish with foam, carbon dioxide, dry powder, or water fog.
- Unsuitable Extinguishing Media:** None known.
- Fire and Explosion Hazard:** None known.
- Hazards during Fire-Fighting:** Hazardous decomposition products may occur when materials polymerize at temperatures above 500 °F (260°C). Irritating and toxic gases/fumes may be released during a fire. Do not allow runoff from fire-fighting to enter drains or water courses.
- Fire-Fighting Procedures:** Use standard firefighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.
- Hazchem Code:** 3Z (part A)/ 2X (part B)
- Combustion Products:** Carbon dioxide. Carbon monoxide. Nitrogen Oxides. Organic Compounds. Acids.

**6. Accidental Release Measures**

**Personal Precautions**

Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

**Clean-Up Methods**

**Small spills:** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.

**Large spills:** Stop the flow of material, if this is without risk. Dike far ahead of spill. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas.

**Environmental Precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

**7. Handling and Storage**

**Handling**

Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Avoid contact with eyes, skin, and clothing. Observe good industrial hygiene practices.

**Storage**

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a dry place out of direct sunlight. Keep out of the reach of children. Store between 45-90°F (7-32°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Store locked up.

**8. Exposure Controls / Personal Protection**

**Personal Protective Equipment**

**Protective Measure:** Wear appropriate personal protective equipment.

**Eye Protection:** Wear chemical splash goggles or safety glasses with side shield.

**Hand Protection:** Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.

**Skin and Body Protection:** Wear long sleeve shirt/long pants and other clothing as required to minimize contact.

**Respirator Protection:** The use of a respirator is not required during normal use of this product. If grinding or cutting cured product the use of a respirator is recommended.

**General Hygiene:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Engineering Controls**

When using indoors good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

**Exposure Limits**

Component	Australia Workplace OELs	New Zealand WES	US. ACGIH (TLV)	South Africa R:1179 (1995) OEL-CL
Titanium dioxide (CAS 13463-67-7)	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Diethylenetriamine (CAS 111-40-0)	1 ppm (TWA)	1 ppm (TWA)	1 ppm (TWA)	1 ppm (TWA)

**Additional Information**

**After Cure:** Product forms an innocuous solid. Processing after cure (grinding or cutting) may produce dust containing compounds that present an inhalation hazard.

**9. Physical and Chemical Properties**

<u>Property</u>	<u>Part A</u>	<u>Part B</u>
Physical State:	Liquid, Paste	Liquid, Paste
Color:	White	Black
Odor:	No Significant Odor	Strong, skunk like
pH:	8.4	10.2
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	>1 torr (356°F, 180°C)	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Appreciable
Freezing/Melting Point:	No data	No data
Boiling Point:	> 392 °F (>200 °C)	No data
Flash Point:	>300 °F (>149 °C) Closed Cup	172 °F (78 °C) Closed Cup
Evaporation Rate:	No data	No data
Decomposition Temperature:	No data	No data
Specific Gravity:	1.56 at 72°F (22°C)	1.55 at 72°F (22°C)
VOC (after cure):	7 g/L	7 g/L
Kow:	No data	No data
Viscosity:	No data	No data

**10. Stability and Reactivity**

**Part A (white side)**

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Strong oxidizing agents. Acids. Amines. Bases, alkalis (organic).
Hazardous Reactions:	Hazardous polymerization does not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

**Part B (black side)**

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Strong oxidizing agents. Strong acids.
Hazardous Reactions:	Hazardous polymerization will not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

**11. Toxicological Information**

**Likely Routes of Exposure**

Ingestion:	Causes digestive tract burns. Ingestion may cause irritation to the gastrointestinal tract.
Inhalation:	Causes respiratory tract burns. If this material is heated or misted, coughing and mild, temporary irritation may occur.
Skin contact:	Causes skin irritation. Causes severe skin burns. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation. Causes serious eye burns.

**Information on Toxicological Effects**

Acute toxicity: Occupational exposure to the substance or mixture may cause adverse effects.

Product	Species	Test Result
o-Cresyl Glycidyl Ether (2210-79-9)	Acute, Dermal, LD50	Rat >2000 mg/kg
	Acute, Inhalation, LC50	Rat >6.1 mg/l, 4 hours
	Acute, Oral, LD50	Rat >5000 mg/kg

Skin corrosion/irritation:	Causes skin irritation.
Eye damage/eye irritation:	Causes serious eye irritation. Causes serious eye damage.
Respiratory sensitization:	No data available.

# ETR Crack Injection Paste-Over Adhesive

## SAFETY DATA SHEET

<b>Skin sensitization:</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity:</b>	Contains a component that is suspected of causing genetic defects.
<b>Carcinogenicity:</b>	Titanium Dioxide is considered a carcinogen only in its inhalable form. Exposure is likely only when grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure. <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b> Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans Wollastonite (CAS 13983-17-0) 3 Not classifiable as to carcinogenicity
<b>Reproductive toxicity:</b>	No data available.
<b>Aspiration hazard:</b>	No data available.
<b>Specific target organ toxicity:</b>	
<b>Single exposure</b>	May cause drowsiness or dizziness.
<b>Repeated exposure</b>	No data available.

### Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

## 12. Ecological Information

### General Information

Information given is based on data on the components and similar products. Part A is classified as toxic to aquatic life with long lasting effects. Part B is not classified as environmentally hazardous. Avoid release to the environment.

### Supporting Data

Component	Species	Test Result
Bisphenol A/Epichlorohydrin (25068-38-6)	Fish, LC50	Salmo Gairdneri 1.5 mg/l, 96 hours
	<b>Aquatic</b> , Crustacea, EC50	Daphnia Magna 2.7 mg/l, 48 hours
Titanium dioxide (CAS 13463-67-7)	<b>Aquatic</b> , Crustacea, EC50	Daphnia >1000 mg/l, 48 hours
	<b>Aquatic</b> , Fish, LC50	Mummichog >1000 mg/l, 96 hours

<b>Persistence and degradability:</b>	This product is not suspected to be readily biodegradable.
<b>Bioaccumulative potential:</b>	No data available for this product.
<b>Mobility in soil:</b>	No data available.

### Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

## 13. Disposal Consideration

<b>Waste Disposal of Substance:</b>	Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Container Disposal:</b>	Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>Disposal of Cured Product:</b>	Grind or chip off surface. Solid material does not need special disposal considerations.

## 14. Transportation Information

### Part A (white side)

<b>UN number:</b>	UN3082
<b>UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant
<b>Transport hazard class(es):</b>	9
<b>Precautions:</b>	Marine Pollutant

# ETR Crack Injection Paste-Over Adhesive

## SAFETY DATA SHEET

**SIMPSON****Strong-Tie**

Packing group:	III
Required Labels:	9
Hazard ID (ADG)	D3Z
ERG Code (IATA):	9L
EmS (IMDG):	F-A, S-F
Hazchem Code:	3Z

### Part B (black side)

UN number:	UN3259
UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (Diethylenetriamine), 8, III
Transport hazard class(es):	8
Precautions:	Corrosive
Packing group:	III
Required Labels:	8
Hazard ID:	2X
ERG Code (IATA):	8L
EmS (IMDG):	F-A, S-B
Hazchem Code:	2X

### Additional Information

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
This substance/mixture is not intended to be transported in bulk.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

## 15. Regulatory Information

### Australian National Regulations

This SDS was prepared following the Code of Practice: Preparation of Safety Data Sheets for Hazardous Chemicals from Work Safe Australia. This product has been classified according to the hazard criteria of GHS and contains all of the information required by WHS.

#### Listing in the Australian Inventory of Chemical Substances

Chemical	AICS Listing
Bisphenol-A-Epichlorohydrin (Epoxy Resin) (CAS 25068-38-6)	Hazardous Substance High Volume Industrial Chemicals List (HVICL)
Wollastonite (CAS 13983-17-0)	Listed
Limestone (CAS 1317-65-3)	High Volume Industrial Chemicals List (HVICL)
o-Cresyl Glycidyl Ether (CAS 2426-08-6) <i>Listed as Oxirane, (butoxymethyl)-</i>	Hazardous Substance
Titanium Dioxide (CAS 13463-67-7) <i>Listed as Titanium Oxide (TiO<sub>2</sub>)</i>	High Volume Industrial Chemicals List (HVICL)
Polymercaptan (CAS N/A)	---
Terpene Hydrocarbon (CAS 8002-09-3) <i>Listed as Oils, pine</i>	Listed
Diethylenetriamine (CAS 111-40-0)	Hazardous Substance International Programme on Chemical Safety - SIDS

### New Zealand National Regulations

New Zealand Code of Practice for the Preparation of Safety Data Sheets (SDS) [No. HSNO CoP 8-1 09-06].  
Classified as hazardous according to the Hazardous Substances (minimum Degrees of Hazard) Regulations 2001.

**HSNO: RESIN: 6.3A Skin Corrosion/Irritation; 6.4A Eye Corrosion/Irritation; 6.5B Skin Sensitization; 6.6B Germ Cell Mutagenicity; 6.9B Specific Target Organ Systemic Effects (narcotic effects); 9.1D Aquatic Toxicity (Acute); 9.1B Aquatic Toxicity (Chronic).**



# ETR Crack Injection Paste-Over Adhesive

## SAFETY DATA SHEET

**SIMPSON****Strong-Tie**

**HARDENER:** 3.1D Flammable Liquid; 8.2B Skin Corrosion/Irritation; 8.3A Eye Corrosion/Irritation; 6.5B Skin Sensitization; 6.9A Specific Target Organ Systemic Toxicity (narcotic effects).

### New Zealand Inventory of Chemicals (NZIoC)

Chemical	Registration Status
Bisphenol-A-Epichlorohydrin (Epoxy Resin) (CAS 25068-38-6)	HSNO Approved (HSR003180)
Wollastonite (CAS 13983-17-0)	May be used as a single component chemical under an appropriate group standard.
Limestone (CAS 1317-65-3)	May be used as a single component chemical under an appropriate group standard.
o-Cresyl Glycidyl Ether (CAS 2426-08-6) <i>Listed as Oxirane, (butoxymethyl)-</i>	HSNO Approved (HSR002921)
Titanium Dioxide (CAS 13463-67-7) <i>Listed as Titanium Oxide (TiO<sub>2</sub>)</i>	May be used as a single component chemical under an appropriate group standard.
Polymercaptan (CAS N/A)	---
Terpene Hydrocarbon (CAS 8002-09-3) <i>Listed as Oils, pine</i>	HSNO Approved (HSR001521)
Diethylenetriamine (CAS 111-40-0)	HSNO Approved (HSR002966)

### South Africa National Regulations

Simpson Strong-Tie South Africa is a subsidiary of Simpson Strong-Tie Australia and relies on the parent company to support many of the services it provides, one of these services is Safety Data Sheets (SDS). This SDS contains all of the relevant information required for the South African market, with the exception of the following information.

Local contact information for South African Poisons Centre – Phone: 0219 316129 or 021 6895227

Local Contact for Simpson Strong-Tie who has access to the SDS sheets - Houston Hank – Phone: 0873 540629

**REGISTERED OFFICE:** Unit 5, Fairway Business Park, Stibitz Street  
Westlake Business Park, Westlake 7945  
Cape Town, Western Province

**POSTAL ADDRESS:** PO Box 281 Bergvliet 7864

**PHONE:** 0873540629

**DIRECTORS:** Michael Herbert & Herbert Kuhn

**REGISTRATION #:** 2012/052288/07

**VAT #:** 4190262362

**South African Safety, Health, and Environmental regulations specific for this product:**

Hazardous Substances Act of 1973 (Act No. 15 of 1973): Not listed.

### International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

### International Inventories

Country or Region	Inventory	On Inventory? (Yes/No)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes



**16. Other Information**

**Date Prepared or Revised:** September 2014  
**Supersedes:** August 2012  
**Prepared By:** Simpson Strong-Tie Co. | 5956 W. Las Positas Blvd Pleasanton, CA 94588 USA

**Abbreviations**

**ACGIH:** American Conference of Governmental Industrial Hygienists  
**AICS:** Australian Inventory of Chemical Substances  
**CAS No.:** Chemical Abstract Service Registry Number  
**ES:** Exposure Standard  
**GHS:** Globally Harmonized System of Classification and Labeling of Chemicals  
**HazChem Code:** Emergency action code of numbers and letters that provide information to emergency services.  
**HEPA:** High-Efficiency Particulate Air  
**HSNO:** Hazardous Substances and New Organisms Act (New Zealand)  
**IARC:** International Agency for Research on Cancer  
**IATA:** International Air Transport Association  
**IMDG:** International Maritime Dangerous Goods code  
**Kow:** Octanol-Water Partition Coefficient  
**NIOSH:** National Institute of Occupational Safety and Health (U.S.)  
**NZIoC:** New Zealand Inventory of Chemicals  
**OELs:** Occupational Exposure Limits  
**PEL:** Permissible Exposure Limit  
**SDS:** Safety Data Sheet  
**STEL:** Short Term Exposure Limit (15 minute Time Weighted Average)  
**STOT:** Specific Target Organ Toxicity (GHS Classification)  
**TLV:** Threshold Limit Value  
**TSCA:** Toxic Substances Control Act (U.S.)  
**TWA:** Time Weighted Average (exposure for 8-hour workday)  
**VOC:** Volatile Organic Compounds  
**WELs:** Workplace Exposure Limits

**Disclaimer**

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2014 Simpson Strong-Tie Company Inc.