

SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET

SIMPSON

Strong-Tie

1. Identification

Product Identification

Product Identifier:	SET-XP (SET-XP10, SET-XP22, SET-XP56, SET-XP650, SET-XP)
Recommended Use:	High Strength Anchoring Adhesive for Cracked and Uncracked Concrete
Use Restrictions:	None Known.
UN Number:	3082
Proper Shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-dimethanamine(MXDA)) 8, II, Marine Pollutant
DG Class:	8 (9)
Packing Group:	II
Hazchem Code:	2X

Company Identification

Company: Simpson Strong-Tie Australia Pty Limited	Company: Simpson Strong-Tie New Zealand
Address: Unit 1/16 Kenoma Place Arndell Park, NSW 2148 Australia	Address: 28 Arrenway Drive Albany, Auckland 0632 New Zealand
Phone: +612 9831 7700	Phone: +64 9 477 4440
Website: www.strongtie.com.au	Website: www.strongtie.co.nz
Emergency: 13 11 26	Emergency: 0800 POISON (0800 764 766)

2. Hazard Identification

General Information

SET-XP Anchoring Adhesive is a two part system. The two parts of this product have been assessed according to GHS and are classified below. The final hardened material is considered nonhazardous. Some hazards apply upon grinding or cutting through hardened product.

Resin (white side) GHS Classification

Classification

Physical Hazards:	Not Classified.	
Health Hazards:	Skin Corrosion/Irritation	Category 2
	Serious Eye Damage/Irritation	Category 2A
	Sensitization, Skin	Category 1
	Germ Cell Mutagenicity	Category 2
Environmental Hazards:	Chronic Aquatic Environmental Hazard	Category 2

Label Elements



Health Hazard



Exclamation Mark



Environment

Signal Word:

WARNING!

Hazard Statements:

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid release to the environment.

Response:

If exposed or concerned: Call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before re-use. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect Spillage.

Storage:

Store locked up. Store in a well-ventilated place. Store between 45-90°F (7-32°C).

Disposal:

Dispose of contents/container in accordance with local/regional/national regulations.

SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET

Hardener (green side) GHS Classification

Classification

Physical Hazards:	Not Classified.	
Health Hazards:	Skin Corrosion/Irritation	Category 1
	Serious Eye Damage/Irritation	Category 1
	Sensitization, Skin	Category 1
	Germ Cell Mutagenicity	Category 2
Environmental Hazards:	Acute Aquatic Environmental Hazard	Category 3
	Chronic Aquatic Environmental Hazard	Category 3

Label Elements



Corrosion



Health Hazard



Exclamation Mark

Signal Word:

DANGER!

Hazard Statements:

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. Harmful to the aquatic environment with long lasting effects.

Precautionary Statements:

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment.

Response:

If exposed or concerned: Get medical advice/attention. If swallowed: Rinse mouth. Do not induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage:

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store between 45-90°F (7-32°C).

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured Resin component of SET-XP. Upon combination with the Hardener component of SET-XP an innocuous solid is formed which does not present any immediate hazards. Upon grinding or cutting the cured product the following hazards may apply.



Health Hazard

Health Hazards:

Carcinogenicity
STOT, Repeated Exposure

Category 1A
Category 2 (Lung)

Hazard Statements:

May cause cancer. May cause damage to organs (Lung) through prolonged or repeated exposure.

Precautionary Statements:

Do not breathe dust.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

SET-XP[®] High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET

SIMPSON
Strong-Tie[®]

Resin (white side)

Chemical Name	CAS Number	Weight %
Bisphenol A/Epichlorohydrin	25068-38-6	40-60
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	40-60
Butyl Glycidyl Ether	2426-08-6	1-10
Titanium Dioxide	13463-67-1	1-10

Hardener (black side)

Chemical Name	CAS Number	Weight %
Silica, crystalline quartz	14808-60-7	20-30
Polyamino Amine	68953-36-6	10-20
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	1-10
Dimethyl silicone polymer with silica	67762-90-7	1-10
Phenol	108-95-2	1-10
Benzene-1,3-Dimethaneamine	1477-55-0	1-10
3,6,9-triazaundecamethylenediamine	112-57-2	1-5

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. You should call the Poisons Information Center if you feel you may have been harmed, burned, or irritated by this product. The number is 13 11 26 (24hr). Ready access to running water and accessible eyewash is required. Wash contaminated clothing before reuse.

Routes of Exposure

- Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician.**
- Skin Contact:** Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. Chemical burns must be treated by a **physician.**
- Ingestion:** Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. **Consult a physician.**
- Inhalation:** Remove patient to fresh air. Oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

Most Important Symptoms

Irritant effects. Sensitization. Symptoms include itching, burning, redness and tearing. Burning pain and severe corrosive skin damage. Causes severe eye damage. May cause temporary blindness and severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause allergic skin reaction. Rash. May cause cancer. Prolonged exposure may cause chronic effects.

5. Fire-Fighting Measures

- Suitable Extinguishing Media:** Extinguish with foam, carbon dioxide, dry powder, or water fog.
- Unsuitable Extinguishing Media:** None known.
- Fire and Explosion Hazard:** No unusual fire or explosion hazards.
- Hazards during Fire-Fighting:** Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Irritating and toxic gases/fumes may be released during a fire. Water run-off can cause environmental damage. Do not allow run-off from fire-fighting to enter drains or water courses.
- Fire-Fighting Procedures:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.
- Hazchem Code:** 3Z (resin) / 2X (hardener)
- Combustion Products:** Carbon dioxide. Carbon monoxide. Nitrogen Oxides. Organic Compounds. Acids.

6. Accidental Release Measures

Personal Precautions

Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Clean-Up Methods

Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.
Large spills: Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Avoid contact with eyes, skin, and clothing. Pregnant women should not work with this product if there is risk of exposure. Observe good industrial hygiene practices.

Storage

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a dry place out of direct sunlight. Keep out of the reach of children. Store between 45-90°F (7-32°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Store locked up.

8. Exposure Controls / Personal Protection

Exposure Limits

Component *Skin Designation	Australia Workplace OELs	New Zealand WES	US. ACGIH (TLV)	South Africa R:1179 (1995) OEL-CL
Quartz** (14808-60-7)	0.1 mg/m ³ (respirable)	0.2 mg/m ³ (respirable)	0.025 mg/m ³ (respirable)	0.4 mg/m ³ (respirable)
Phenol* (CAS 108-95-2)	1 ppm	5 ppm	5 ppm	5ppm
m-Phenylenebis(methylamine)* (CAS 1477-55-0)	0.1 mg/m ³ (Ceiling)	0.1 mg/m ³ (Ceiling)	0.1 mg/m ³ (Ceiling)	0.1 mg/m ³ (Ceiling)
N-Butyl Glycidyl Ether (2426-08-6)	25 ppm	25 ppm	3 ppm	25 ppm
Titanium Dioxide** (13463-67-7)	10 mg/m ³	10 mg/m ³	10 mg/m ³	5 mg/m ³ (respirable) 10 mg/m ³ (total dust)

*Skin Designation: Material can be absorbed through the skin.

**After Cure Hazard: After cure hazard, avoid inhalation of dust.

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.
Eye Protection: Wear chemical splash goggles or safety glasses with side shield.
Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.
Respirator Protection: The use of a respirator is not required during normal use of this product. If grinding or cutting cured product the use of an approved respirator is recommended.
General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET

SIMPSON

Strong-Tie®

Engineering Controls

When using indoors good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

Additional Information

After Cure: Product forms an innocuous solid. Processing after cure (grinding or cutting) may produce dust containing compounds that present an inhalation hazard.

9. Physical and Chemical Properties

<u>Property</u>	<u>Resin</u>	<u>Hardener</u>
Physical State:	Liquid, Paste	Liquid, Paste
Color:	White	Dark Green
Odor:	Sweet	Ammonia
pH:	6.9	10.3
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	Non-volatile	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Slightly soluble in water
Freezing/Melting Point:	No data	No data
Boiling Point:	> 500 °F (>260 °C)	No data
Flash Point:	250 °F (121 °C) Open Cup	262 °F (128 °C) Closed Cup
Evaporation Rate:	No data	No data
Decomposition Temperature:	No data	No data
Specific Gravity:	1.21 at 72°F (22°C)	1.59 at 72°F (22°C)
VOC (after cure):	3 g/L	3 g/L
Kow:	No data	No data
Viscosity:	No data	No data

10. Stability and Reactivity

Resin (white side)

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Oxidizing agents, acids, organic bases, and amines
Hazardous Reactions:	Hazardous polymerization does not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

Hardener (green side)

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Strong oxidizing agents. Peroxides. Phenols. Acids.
Hazardous Reactions:	Hazardous polymerization does not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	May be harmful if swallowed. Ingestion may cause irritation to the gastrointestinal tract.
Inhalation:	May cause respiratory irritation
Skin contact:	Causes skin irritation. Causes severe skin burns. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation. Causes severe eye damage.

Information on Toxicological Effects

Acute toxicity: Occupational exposure to the substance or mixture may cause adverse effects.

Product	Species	Test Result
SET-XP Resin (CAS mixture)	Rabbit	>2000 mg/kg
	Rat	>5000 mg/kg

SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET



Product	Species	Test Result
SET-XP Hardener (CAS mixture)	Rabbit	>2000 mg/kg
	Rat	>5000 mg/kg

Skin corrosion/irritation: Causes severe skin burns.
Eye damage/eye irritation: Causes severe eye damage.
Respiratory sensitization: No data available.
Skin sensitization: May cause an allergic skin reaction.
Germ cell mutagenicity: Contains a component that is suspected of causing genetic defects.
Carcinogenicity: May cause cancer. Quartz and Titanium Dioxide are considered carcinogens only in their inhalable form. Exposure to respirable Quartz and Titanium Dioxide is likely only when grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (14808-60-7) 1 Carcinogenic to humans.
 Titanium Dioxide (13463-67-7) 2B Possibly Carcinogenic to humans.
 Phenol (108-95-2) 3 Not classifiable as to carcinogenicity in humans.

NTP Report on Carcinogens

Quartz (14808-60-7) Known to be Human Carcinogen

Reproductive toxicity: No data available.
Aspiration hazard: No data available.
Specific target organ toxicity:
 Single exposure No data available.
 Repeated exposure May cause damage to organs (lung) through prolonged or repeated exposure.

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. Resin is classified as toxic to aquatic life with long lasting effects. Hardener is classified as harmful to aquatic life with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Species	Test Result
SET-XP Resin (CAS mixture)	Algae	>1000 mg/l, 72 hours
	Daphnia Magna	324.87 mg/l, 48 hours
	Fish	707.11 mg/l, 96 hours
Phenol (108-95-2)	Daphnia	4.7-6.4 mg/l, 48 hours
	Rainbow trout	7.5-14 mg/l, 96 hours

Persistence and degradability: This product is not expected to be readily biodegradable.
Bioaccumulative potential: No data available for this product.

Partition coefficient n-octanol / water (log Kow)

Butyl glycidyl ether (2426-08-6) 0.63
 Phenol (108-95-2) 1.46

Mobility in soil: This product is non-volatile.

Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Consideration

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Grind or chip off surface. Solid material does not require special disposal.

14. Transportation Information

Resin (white side)

UN number: UN3082
UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant
Transport hazard class(es): 9
Precautions: Marine Pollutant
Packing group: III
Required Labels: 9
Hazard ID (ADG): D3Z
ERG Code (IATA): 9L
EmS (IMDG): F-A, S-F
Hazchem Code: 2Y

Hardener (black side)

UN number: UN2735
UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-Dimethaneamine), 8, II
Transport hazard class(es): 8
Precautions: Corrosive
Packing group: III
Required Labels: 8
Hazard ID: 2X
ERG Code (IATA): 8L
EmS (IMDG): F-A, S-B
Hazchem Code: 2X

Additional Information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

Australian National Regulations

This SDS was prepared following the Code of Practice: Preparation of Safety Data Sheets for Hazardous Chemicals from Work Safe Australia. This product has been classified according to the hazard criteria of GHS and contains all of the information required by WHS.

No poisons schedule number was allocated for any Australian Medicines & Poisons Appendix.

Listing in the Australian Inventory of Chemical Substances

Chemical	AICS Listing
Butyl Glycidyl Ether (CAS 2426-08-6) <i>Listed as Oxirane, (butoxymethyl)-</i>	Hazardous Substance
Phenol, polymer with formaldehyde, glycidyl ether	Listed

(CAS 28064-14-4)	
Bisphenol A/Epichlorohydrin Resin (CAS 25068-38-6) <i>Listed as Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane</i>	Hazardous Substance High Volume Industrial Chemicals List (HVICL)
Titanium Dioxide (CAS 13463-67-7) <i>Listed as Titanium Oxide (TiO2)</i>	High Volume Industrial Chemicals List (HVICL)
Crystalline Silica, Quartz (CAS 14808-60-7)	Hazardous Substance International Program on Chemical Safety (IPCS) – CICAD High Volume Industrial Chemicals List (HVICL)
Fatty Acids, C18-unsatd., Dimers, Polymers With Tall-oil Fatty Acids and Triethylenetetramine (CAS 68082-29-1)	
2,4,6-Tris(dimethylaminomethyl)phenol (CAS 90-72-2)	Hazardous Substance
Dimethyl silicone polymer with silica (CAS 67762-90-7)	
Phenol (CAS 108-95-2)	
Benzene-1,3-Dimethanamine (CAS 1477-55-0)	Hazardous Substance International Program on Chemical Safety (IPCS) – SIDS High Volume Industrial Chemicals List (HVICL)

New Zealand National Regulations

New Zealand Code of Practice for the Preparation of Safety Data Sheets (SDS) [No. HSNO CoP 8-1 09-06].
Classified as hazardous according to the Hazardous Substances (minimum Degrees of Hazard) Regulations 2001.

HSNO: RESIN: 6.3A Skin Corrosion/Irritation; 6.4A Eye Corrosion/Irritation; 6.5B Skin Sensitization; 6.6B Germ Cell Mutagenicity; 9.1B Aquatic Toxicity (Chronic). HARDENER: 6.1D Acute Toxicity (Dermal); 8.2B Skin Corrosion/Irritation; 8.3A Eye Corrosion/Irritation; 6.5B Skin Sensitization; 6.8B Reproductive Toxicity; 9.1A Aquatic Toxicity (Acute); 9.1B Aquatic Toxicity (Chronic).

New Zealand Inventory of Chemicals (NZIoC)

Chemical	Registration Status
Butyl Glycidyl Ether (CAS 2426-08-6) <i>Listed as Oxirane, (butoxymethyl)-</i>	HSNO Approved (HSR002921)
Phenol, polymer with formaldehyde, glycidyl ether (CAS 28064-14-4)	May be used as a single component chemical under an appropriate group standard.
Bisphenol A/Epichlorohydrin Resin (CAS 25068-38-6) <i>Listed as Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane</i>	HSNO Approved (HSR003180)
Titanium Dioxide (CAS 13463-67-7) <i>Listed as Titanium Oxide (TiO2)</i>	May be used as a single component chemical under an appropriate group standard.
Crystalline Silica, Quartz (CAS 14808-60-7)	HSNO Approved (HSR003125)
Fatty Acids, C18-unsatd., Dimers, Polymers With Tall-oil Fatty Acids and Triethylenetetramine (CAS 68082-29-1)	
2,4,6-Tris(dimethylaminomethyl)phenol (CAS 90-72-2)	HSNO Approved (HSR003549)
Dimethyl silicone polymer with silica (CAS 67762-90-7)	
Phenol (CAS 108-95-2)	
Benzene-1,3-Dimethanamine (CAS 1477-55-0)	May be used as a single component under an appropriate group standard

South Africa National Regulations

Simpson Strong-Tie South Africa is a subsidiary of Simpson Strong-Tie Australia and relies on the parent company to support many of the services it provides, one of these services is Safety Data Sheets (SDS). This SDS contains all of the relevant information required for the South African market, with the exception of the following information.

SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET



Local contact information for South African Poisons Centre – Phone: 0219 316129 or 021 6895227
Local Contact for Simpson Strong-Tie who has access to the SDS sheets - Houston Hank – Phone: 0873 540629

REGISTERED OFFICE: Unit 5, Fairway Business Park, Stibitz Street
Westlake Business Park, Westlake 7945
Cape Town, Western Province

POSTAL ADDRESS: PO Box 281 Bergvliet 7864

PHONE: 0873540629

DIRECTORS: Michael Herbert & Herbert Kuhn

REGISTRATION #: 2012/052288/07

VAT #: 4190262362

South African Safety, Health, and Environmental regulations specific for this product:
Hazardous Substances Act of 1973 (Act No. 15 of 1973): Not listed.

International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Country or Region	Inventory	On Inventory? (Yes/No)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

16. Other Information

Date Prepared or Revised: October 2014
Supersedes: August 2012

Abbreviations

ACGIH: American Conference of Governmental Industrial Hygienists
CAS No.: Chemical Abstract Service Registry Number
CERCLA: Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
CPR: Controlled Product Regulations (Canada)
DOT: Department of Transportation (U.S.)
EPA: Environmental Protection Agency (U.S.)
GHS: Globally Harmonized System of Classification and Labeling of Chemicals
HEPA: High-Efficiency Particulate Air
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
IMDG: International Maritime Dangerous Goods code
LPP: Limité Permissible Ponderado (Chile)
NIOSH: National Institute of Occupational Safety and Health (U.S.)
NFPA: National Fire Protection Association (US)
NTP: National Toxicology Program (US)
OSHA: Occupational Safety and Health Administration (U.S.)
PEL: Permissible Exposure Limit
SARA: Superfund Amendments and Reauthorization Act (U.S. EPA)

SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

SAFETY DATA SHEET



SDS:	Safety Data Sheet
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
U.S.:	United States
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2014 Simpson Strong-Tie Company Inc.